

## SLITTER-REWINDER EASYline US-320/420

for converting and checking  
of narrow web materials:



### 1) Steel plate construction

- Welded steel frame
- Covered with painted steel plates
- Front and bottom plate made of steel
- Sides and covers made of sheet steel
- Electronics integrated in the machine housing
- Supply 240 volts

## 2) Unwinder with pneumatic air shaft

- Magnetic powder brake
- Right / left unwinding possible
- Tension can be adjusted manually
- Pneumatic air shaft 76 mm
- Roll diameter max. Ø 500 mm
- Coil weight max. 80 kg
- Material width 50 mm to 320/420 mm

## 3) Splice table

- Splice table from sheet steel
- Four magnetic clamping jaws
- Knife guide for cross or diagonal cut

## 4) Web guiding system

- By two photoelectric sensor

## 5) Counter

- Changeable from label counter to meter counter

## 6) Drive unit

- Steel roller
- Rubberized pressure roller
- Adjustable pressure of the pressure roller
- Driven by electric motors
- Web speed up to 120m/min, depending on the product

## 7) suction

- Axial fan for suction of waste strip

## 8) slitter

- Scissor cutting system with rotary blades
- Eight pieces of upper blade
- Eight pieces anvil blade rings
- Minimum cutting width 18mm / 10mm as option



### 9) 2 piece rewinding shafts

- Pneumatic air shaft for 3 inch cores  
Other diameter are option
- Tension adjustable by magnetic powder clutch
- Roll diameter max. 480 mm
- Max. axle weight 80 kg

### 10) Web holder

- Rubered Roller as web holder  
to fix the web when change the rolls at rewinder
- Switch for open and close
- Automatically open when start the machine

### 11) Operating and control unit

- Main switch
- Control "ON" button
- START / STOP button
- Emergency Stop button
- Variable speed by potentiometer
- Meter and label counter switchable
- Lettering in English or local language
- Automatic machine stop when reaching the pre-selected number of meters / labels
- Electronic components integrated in the machine housing
- Web direction from left to right
- Manual and Dokumentation in English or local language
- CE Declaration of Conformity

**12)Material to be processed**

- Adhesive labels, paper, foil, laminates up to 600 grs/m<sup>2</sup>

**Total price of the machine****see offer****Technical data:**

Voltage:	240 Volt
Electrical power:	1,8 / 2,2 KW
Current:	10 Amps
Frequency:	50 Hz
Pneumatic air supply:	6 bars
Length x width x height:	1.100 mm x 900/1.000 mm x 1.300 mm
Weight:	about 530/600 kg

**Optionen:**

- Airshaft from 19 mm up to 6 Inch
- Frictionsshafts
- Clockwise/Other clockwise switchable
- Pneumatic knife holder
- Razor blade holder
- Back slit Unit
- Narrow slitter from ab 3 mm
- Label counter for clear of clear Material
- Finishing for slit tapes and materials with open gluing