

SLITTER-REWINDER EASYline US-550

for converting and checking
of narrow web materials:



1) Steel plate construction

- Welded steel frame
- Covered with painted steel plates
- Front and bottom plate made of steel
- Sides and covers made of sheet steel
- Electronics integrated in the machine housing
- Supply 400 volts

2) Unwinder with pneumatic air shaft

- Magnetic powder brake
- Right / left unwinding possible
- Tension can be adjusted manually
- Pneumatic air shaft 76 mm
- Roll diameter max. Ø 700 mm
- Coil weight max. 250 kg
- Material width 50 mm to 570 mm



3) Splice table

- Splice table from sheet steel
- Four magnetic clamping jaws
- Knife guide for cross or diagonal cut



4) Web guiding system

- By two photoelectric sensor

5) Counter

- Changeable from label counter to meter counter

6) Drive unit

- Steel roller
- Rubberized pressure roller
- Adjustable pressure of the pressure roller
- Driven by electric motors
- Web speed up to 120m/min, depending on the product

7) suction

- Axial fan for suction of waste strip

8) slitter

- Scissor cutting system with rotary blades
- Eight pieces of upper blade
- Eight pieces anvil blade rings
- Minimum cutting width 18mm / 10mm as option



9) 2 piece rewinding shafts

- Pneumatic air shaft for 3 inch cores
- Tension adjustable by magnetic powder clutch
- Roll diameter max. 600 mm
- Max. axle weight 160 kg



10) Web holder

- Rubered Roller as web holder to fix the web when change the rolls at rewinder
- Switch for open and close
- Automatically open when start the machine

11) Operating and control unit

- Main switch
- Control "ON" button
- START / STOP button
- Emergency Stop button
- Variable speed by potentiometer
- Meter and label counter switchable
- Lettering in English or local language
- Automatic machine stop when reaching the pre-selected number of meters / labels
- Electronic components integrated in the machine housing
- Web direction from left to right
- Manual and Dokumentation in English or local language
- CE Declaration of Conformity

12) Material to be processed

- Adhesive labels, paper, foil, laminates up to 800 grs/m²

Total price of the machine

see offer

Technical data:

Voltage:	400 Volt
Electrical power:	2,5 KW
Current:	12 Amps
Frequency:	50 Hz
Pneumatic air supply:	6 bars
Length x width x height:	1.400 mm x 960 mm x 1,500 mm
Weight:	about 840 kg

Optionen:

- Airshaft from 1 Inch up to 6 Inch
- Frictionshafts
- Clockwise/Other clockwise switchable
- Pneumatic knife holder
- Razor blade holder
- Back slit Unit
- Narrow slitter from ab 3 mm
- Label counter for clear of clear Material
- Finishing for slit tapes and materials with open gluing